

# Motorcycle Wheel Force Transducer, 6-Axis

## Model LW-MC-3.5K

- 3,500 lb (15.5 kN) radial load capacity
- 1,200 lb (5.3 kN) lateral load capacity
- Measures 3 Forces and 3 Moments
- Wireless Telemetry and Induction System  
CAN, Analog, and Ethernet signal outputs
- Adapts to 11" and larger wheels
- Low cross axis sensitivity
- Temperature compensated
- Remove wheel without removing electronics



## Description

The LW-MC-3.5K Wheel Force Transducer (WFT) is capable of measuring all of the wheel forces and moments on a motorcycle. It provides independent output signals for vertical, lateral, and longitudinal forces as well as camber, steer, and torque moments. It is completely weatherproof making it ideal for testing in any weather conditions.

The Telemetry electronics, Induction Power electronics, and Magnetic encoder wheel are packaged into the transducer to create a low profile and durable assembly.

The CT2-TEL Transducer Telemetry Interface Box performs real-time coordinate transformation and cross-talk compensation, and outputs analog, CAN, and Ethernet signals. An embedded web page allows the user to configure the WFT System.

## Specifications

Maximum Force Capacity, [Fx, Fz] Radial	3,500 lb (15.5 kN)
[Fy] Lateral at Tire Patch	1,200 lb (5.3 kN)
Maximum Moments Capacity [Mx, Mz]	1,200 lb-ft (1.6 kN-m)
[My] Wheel Torque	2,500 lb.ft (3.4 kN-m)
Sensor	4 arm strain gage bridges
Nonlinearity	< 1% of full scale output
Hysteresis	< 0.5% of full scale output
Repeatability	< 0.5% of full scale output
Cross Axis Sensitivity After Compensation	< 1% of full scale output
Radial Sensitivity Variation	< 1% of full scale output
Transducer Temperature Range, Operating	-40°F to 257°F (-40°C to 125°C)
CT2-TEL Temperature Range	-5°F to 140°F (-20°C to 60°C)
Weight (Transducer & Telemetry Electronics)	5.0 lb (2.25 kg)
Angular Resolution	0.25°
Transmission Rate of Data	2,200 Hz
Data Bandwidth	200 Hz (<-0.1 dB) ; 500 Hz (<-1.0 dB)
Data Resolution	16 bit
System Delay on Analog Channels	20.69 ms
Anti-Alias filter type	Bessel Linear Phase
Input Power Requirements	10-36 VDC, ~2.0 Amps @ 13.5 VDC Typ.

8500 Ance Road  
Charlevoix, MI 49720  
Tel: 231-547-5511  
Fax: 231-547-7070

10/17/13

Rev. A

**MICHIGAN SCIENTIFIC**  
corporation

<http://www.michsci.com>

Email: [mscinfo@michsci.com](mailto:mscinfo@michsci.com)

321 East Huron Street  
Milford, MI 48381  
Tel: 248-685-3939  
Fax: 248-684-5406



+33 (0)1 46 91 93 32

Capteurs et Systèmes de mesure

59, rue Émile Deschanel - 92400 COURBEVOIE - France - Fax : 33 (0)1 46 91 93 39 - [contact@pm-instrumentation.com](mailto:contact@pm-instrumentation.com)

# Motorcycle Wheel Force Transducer, 6-Axis

## CT2 Transducer Interface Box

- Performs real-time coordinate transformation and cross-talk compensation
- Easy to use Zero, Shunt Calibration, and Bridge Power Off functions
- Provides power to Induction System
- Simultaneous Analog, CAN, & Ethernet signal outputs
- Embedded web page enables user to:
  - Change set-up options
  - Move WFT measurement origin
  - View Transducer static values
  - Create .dbc file



## Telemetry Stator

- Receives and Decodes the telemetry signal from the Transducer
- Provides High Resolution Speed & Position Signals
- Mounts outboard of the Transducer



8500 Ance Road  
Charlevoix, MI 49720  
Tel: 231-547-5511  
Fax: 231-547-7070  
10/17/13

Rev. A

**MICHIGAN SCIENTIFIC**  
corporation

<http://www.michsci.com>  
Email: [mscinfo@michsci.com](mailto:mscinfo@michsci.com)

321 East Huron Street  
Milford, MI 48381  
Tel: 248-685-3939  
Fax: 248-684-5406



+33 (0)1 46 91 93 32 **Capteurs et Systèmes de mesure**

59, rue Émile Deschanel - 92400 COURBEVOIE - France - Fax : 33 (0)1 46 91 93 39 - [contact@pm-instrumentation.com](mailto:contact@pm-instrumentation.com)