

Wheel Force Transducer, 6-Axis

Model LW15.0

- 14,000 lb (62.2 kN) radial load capacity
- 7,000 lb (31.1 kN) lateral load capacity
- Measures 3 forces and 3 moments
- Measures X & Z accelerations
- Adapts to 15" and larger wheels
- Low cross axis sensitivity
- Environmentally protected
- Temperature compensated
- Rugged stainless steel construction



Description

The LW15.0 Wheel Force Transducer (WFT) is capable of measuring all of the wheel forces and moments on passenger cars and light duty trucks. It provides independent output signals for vertical, lateral, and longitudinal forces as well as camber, steer, and torque moments. Being completely weatherproof, it is ideal for on-road and off-road measurements in all conditions. It can also be used to monitor and control laboratory tests.

The matching amplifier package easily mounts onto the transducer. It amplifies and digitizes the transducer signals before they pass through the slip ring. The amplifier package also includes X and Z acceleration outputs and performs remote shunt calibration of the transducer.

The CT2 Transducer Interface Box performs real-time coordinate transformation and cross-talk compensation, and outputs analog, CAN, and Ethernet signals. An embedded web page allows the user to configure the WFT system.

Specifications

Maximum Force Capacity [Fx, Fz] Radial	14,000 lb (62.2 kN)
[Fy] Lateral at Tire Patch	7,000 lb (31.1 kN)
Maximum Torque Capacity, [Mx, My, Mz]	7,000 lb-ft (9,500 N-m)
Accelerometer range	+ 55g
Sensor	4 arm strain gage bridges
Nonlinearity	<1% of full scale output
Hysteresis	<0.5% of full scale output
Repeatability	Within 0.5% of full scale output
Cross Axis Sensitivity after correction	<1% of full-scale output
Radial Sensitivity Variation	<1% of full scale output
Temperature Range, Operating	-40°F to 257°F (-40°C to 125°C)
Angular Resolution	0.17°



+33 (0)1 46 91 93 32 Capteurs et Systèmes de mesure

59, rue Émile Deschanel - 92400 COURBEVOIE - France - Fax : 33 (0)1 46 91 93 39 - contact@pm-instrumentation.com

8500 Ance Road
Charlevoix, MI 49720
Tel: 231-547-5511
Fax: 231-547-7070

MICHIGAN SCIENTIFIC
corporation
<http://www.michsci.com>
Email: mscinfo@michsci.com

321 East Huron Street
Milford, MI 48381
Tel: 248-685-3939
Fax: 248-684-5406

4/13/13

Rev. A

Wheel Force Transducer, 6-Axis

CT2 Transducer Interface Box

- Performs real-time coordinate transformation and cross-talk compensation
- Easy to use Zero, Shunt Calibration, and Bridge Power Off functions
- Simultaneous Analog, CAN, & Ethernet signal outputs
- Embedded web page enables user to:
 - Change set-up options
 - Move WFT measurement origin
 - View Transducer static values
 - Create .dbc file



Amplifier & Slip Ring Package

- Internal X & Z accelerometers
- High resolution encoder for position & speed measurement
- Internal smart chip contains all calibration, zero, & shunt values
- Provides signal conditioning & amplification to the transducer strain gage signals
- Digitizes Transducer, Encoder, & Accelerometer signals
- Supports slip ring



8500 Ance Road
Charlevoix, MI 49720
Tel: 231-547-5511
Fax: 231-547-7070
4/13/13

MICHIGAN SCIENTIFIC
corporation

<http://www.michsci.com>
Email: mscinfo@michsci.com

321 East Huron Street
Milford, MI 48381
Tel: 248-685-3939
Fax: 248-684-5406

Rev. A



+33 (0)1 46 91 93 32

Capteurs et Systèmes de mesure

59, rue Émile Deschanel - 92400 COURBEVOIE - France - Fax : 33 (0)1 46 91 93 39 - contact@pm-instrumentation.com